



levian.it

LEVIAN Srl

Valvole Antincendio
Fire-Fighting Valves

HP VALVE WITH SWINGING LEVER



69-450-01XX

Brass valve with metal swinging lever

Extinguishing agent : CO₂ / NITROGEN / ARGON

FEATURES :

TEMPERATURE RANGE	CYLINDER CONNECTION	OUTLET CONNECTION	DIP TUBE CONNECTION	BURST DISK CALIBRATIONS	PRESSURE RESISTANCE	CERTIFICATIONS
-30 / +60° C	W28.8 25E W19.8 17E	W21.7x1.814	1/4G ; 1/8G M14 ; M10	200 / 225 / 250 bar	750 bar	EN 3 97/23/CE PED 2010/35/UE TPED

MATERIALS :

Valve body : Brass

Protective treatments : Nickel plating

Levers : Stainless steel **6 mm thick** ; available in different lengths and shapes

Spring : Stainless steel

Rivet : Stainless steel

Dip tube adapter : Brass - **removable**

ACCESSORIES :

Safety pin : Metal wire Ø 4mm ; Zinc plated steel or Stainless steel

Safety pin seal : Thermoplastic , available in different colors

Overpressure indicator : Thermoplastic , available in different colors

Cable actuation path : Stainless steel

THREAD COATING : Sealant application, **4 years shelf life** if stocked in humidity max 60%



NICKEL PLATED



CABLE ACTUATION - FRONT



CABLE ACTUATION - BACK