



levian.it

LEVIAN Srl

Valvole Antincendio
Fire-Fighting Valves

CO2 / INERT GASES

FIX INTASTALLATIONS VALVE



69-450-20XX

Differential pressure brass valve

Suppression agent : CO2 / INERT GASES

FEATURES :

TEMPERATURE RANGE	CYLINDER CONNECTION	OUTLET CONNECTION	DIP TUBE CONNECTION	BURST DISK CALIBRATIONS	PRESSURE RESISTANCE	CERTIFICATIONS
-30 / +60° C	W28.8 25E	W21.7x1.814	3/8 ; 1/4 ; 1/8 G M14 ; M10	200 / 360 bar	750 bar	97/23/CE PED 2010/35/UE TPED

SPECIFICATION :

Valve body material : Brass

Protective treatments : Nickel plating

Outlet $\varnothing$: 14 mm

Operation method : Complete discharge

Actuation method : Rupture disk or non-return valve ; 1 to 3 actuators

Pressure switch connection : 1/4 G

Pressure interception connection : 1/4 G

ACCESSORIES :

Electric actuator : Solenoid valve or pyrotechnic cartridge gas generator

Pneumatic actuator : Brass, operating pressure 6 to 60 bar

Manual actuator : Brass with stainless steel swinging lever

Safety pin : Metal wire $\varnothing$ 4mm ; Zinc plated steel or Stainless steel

Safety pin seal : Thermoplastic , available in different colors

Overpressure indicator : Thermoplastic , available in different colors

Outlet protection cap : Brass

Actuation cap screwing key : nickel plated brass sector key

Charge/Relief device : Brass non-return valve with protection cap

Charge/Relief adapter : Stainless steel, 1/4 G ; W 21.7

THREAD COATING : Sealant application, **4 years shelf life** if stocked in humidity max 60%