

PERMANENT PRESSURE WHEELED EXTINGUISHERS VALVE



69-450-03XX

Brass valve with metal lever

Extinguishing agent : POWDER / WATER BASED

FEATURES :

TEMPERATURE RANGE	CYLINDER CONNECTION	OUTLET CONNECTION	DIP TUBE CONNECTION	MANOMETER CONNECTION	PRESSURE RESISTANCE	CERTIFICATIONS
-30 / +60° C	M52x1.5 MALE G2" FEMALE	M18x1 3/8" G	M33x1.5 M22x1.5	M10x1	300 bar	EN 3 97/23/CE PED

MATERIALS :

Valve body : Brass

Protective treatments : Aggressive agents coating **1.000h salt spray test resistance**

Levers : Stainless steel

Spring : Stainless steel

Rivet : Stainless steel

Dip tube adapter : Zinc plated steel only M22x1.5 threads –**removable**

Pressure Relief Device : 17-23 bar at 20°C

Check valve : M10x1

Safety pin : Metal wire Ø 4mm ; Zinc plated steel or Stainless steel

Safety pin seal : Thermoplastic , available in different colors

Filter : Sintered bronze

O-ring : M52 cylinder connection size

Pressure gauge : Nickel plated brass or Stainless steel , available with different scales

Dip tube : Thermoplastic , available in different lengths